

# PLAIN PAPER FAX Phone & Copier

10 Page Auto Document Feed

50 Sheet Paper Cassette

512K Memory Stores up to 25 Pages\* for Out-of-Paper Reception

Auto FAX/TEL switching for receiving fax and voice calls on a single phone line

Easy to change Replacement Print Cartridge prints up to 150 pages



©2000 Brother International Corporation

PLAIN PAPER FAX PHONE & COPIER

BOROK

## **FEATURING**

- 10 Page Auto Document Feed
- 50 Sheet Paper Cassette
- 512K Memory, stores up to 25 Pages\* for Out-of-Paper Reception
- Quick Scan faxes for memory transmission
- Broadcast a fax to up to 54 locations
- Multi-copying up to 99 copies, plus Sorting
- Copy Reduction and Enlargement (50% 150%)
- Auto FAX/TEL Switching lets you receive fax and voice calls on a single phone line
- 54 Station Auto Dialing
- Fax Forwarding, Paging and Remote Retrieval
- Call Waiting/Caller ID and Distinctive Ring Detection Ready\*\*
- "One-Touch" access to the CallManage<sup>™</sup> low long distance rate program<sup>†</sup>
- Easy to change Replacement Print Cartridge prints up to 150 pages (Item PC401)

### **OTHER STANDARD FEATURES**

- Answering Machine Interface
- 64 Shade Gray Scale for Photo Transmission
- "Smoothing" Enhanced Image Resolution
- Electronic Cover Page
- Multiple Resolution Transmission
- Enhanced Remote Activation
- Next-Fax Reservation
- Error Correction Mode (ECM)
- Search stored Auto Dial numbers alphabetically
- Auto Reduction of incoming faxes
- Polling and Delayed Transmission



1-888-387-9680



#### **PRODUCT SPECIFICATIONS**

Approved: UL and FCC Unit Dimensions: 13.2" x 11.9" x 11.1" Carton Dimensions: 15.9" x 13.2" x 9.1" Unit/Carton Weight: 7.3 lbs. / 9 lbs. UPC Code: 012502565031 Compatibility: ITU-TS Group 3 Coding Method: MH Modulation: 9600/7200/4800/2400 bps Transmission Time: 15 seconds (8.5" x 11") Document Input Width: 5.8" to 8.5" Recording Paper Size: 8.5" x 11" / 8.5" x 14" Scanning/Printing Width: 8.2" Fax Resolution: Standard: 203 x 98 lines/inch Fine/Photo: 203 x 196 lines/inch Superfine/Photo: 203 x 392 lines/inch Display: LCD, 16 characters Dialing System: Tone Speaker Type: Monitor Communication Source: Public Switched Telephone Network Connection Requirements: USOC RJ11C Modular Jack (or equivalent) Power Supply: 120V, 50/60 Hz Power Consumption: Standby: Under 5W Peak: Under 170W Operating Environment: 41° - 95° F

### OPTIONAL ACCESSORIES<sup>4</sup> PC401: Printing Cartridge PC402RF: 2-Refill Ribbon Rolls



\* Using ITU-T Test Chart #1 at standard resolution in error

- correction mode. \*\* Contact local phone company for availability of these services.
- Requires additional purchase.
- Requires registration with CallManage, Inc. See Owner's Manual for complete terms and conditions.

FOR MORE INFORMATION PLEASE CALL THE BROTHER FAX-BACK SYSTEM AT 1-800-521-2846 (USA), 1-800-681-9838 (CANADA) OR VISIT OUR WEB SITE AT http://www.brother.com

At your sidë. **booble** 100 Somerset Corporate Blvd., Bridgewater, NJ 08807-0911 All specifications subject to change without notice. Printed in the USA. CATEX560

© 2000 BROTHER INTERNATIONAL CORPORATION