Scheduled Maintenance

Follow Schedule 1 if the vehicle is operated mainly where none of the following conditions apply.

If any do apply, follow Schedule 2 (Canada and Puerto Rico residents follow Schedule 2).

- Repeated short-distance driving
- Driving in dusty conditions
- Driving with extended use of brakes
- Driving in areas where salt or other corrosive materials are being used
- Driving on rough or muddy roads
- Extended periods of idling or low-speed operation
- Driving for long periods in cold temperatures or extremely humid climates

NOTE

After the prescribed period, continue to follow the described maintenance at the recommended intervals.

Maintenance and Care

▼Schedule 1

I : Inspect and repair, clean, adjust, or replace if necessary.
R: Replace
L: Lubricate

Maintenance Interval	Months	6	12	18	24	30	36	42	48
(Number of months or kilometers (miles),	×1000 km	12	24	36	48	60	72	84	96
whichever comes first)	×1000 miles	7.5	15	22.5	30	37.5	45	52.5	60
ENGINE									
	2.3-liter engine					Ι			
Drive belts (tension)	3.0-liter engine				Ι				Ι
Engine oil	•	R	R	R	R	R	R	R	R
Engine oil filter		R	R	R	R	R	R	R	R
COOLING SYSTEM									
Cooling system					Ι				Ι
Engine coolant								or 60 m or 24 mo	
FUEL SYSTEM									
Air filter						R			
Fuel lines and hoses ^{*1}					Ι				Ι
Hoses and tubes for emis	sion ^{*1}								Ι
IGNITION SYSTEM									
Spark plugs			Repl	ace eve	ry 120,	000km ((75,000	miles)	
CHASSIS and BODY									
Brake lines, hoses and co	nnections				Ι				Ι
Disc brakes			Ι		Ι		Ι		Ι
Steering operation and lir	ıkages				Ι				Ι
Front suspension ball joir					Ι				Ι
Driveshaft dust boots					Ι				Ι
Bolts and nuts on chassis	and body				Ι				Ι
	lds				Ι				Ι
Exhaust system heat shiel			Ŧ	T	L	L	L	L	L
		L	L	L	L	L	L	L	
Exhaust system heat shiel		L	L	L	L	L	L	Ľ	L

According to state/provincial and federal regulations, failure to perform maintenance on these items will not void your emissions warranties. However, Mazda recommends that all maintenance services be performed at the recommended time or mileage/kilometer period to ensure long-term reliability. 1

▼ Schedule 2

 ${\bf I}$: Inspect and repair, clean, adjust, or replace if necessary.

R: Replace

Maintenance Interval	Months	4	8	12	16	20	24	28	32	36	40	44	48
(Number of months or kilometers (miles),	×1000 km	8	16	24	32	40	48	56	64	72	80	88	96
whichever comes first)	×1000 miles	5	10	15	20	25	30	35	40	45	50	55	60

ENGINE

Drive belts (tension)	2.3-liter engine							Ι					
Drive bens (tension)	3.0-liter engine						Ι						Ι
Engine oil	Puerto Rico	Replace every 5,000km (3,000miles) or 3 months											
Engine on	Others	R	R	R	R	R	R	R	R	R	R	R	R
Engine oil filter		R	R	R	R	R	R	R	R	R	R	R	R

COOLING SYSTEM

Cooling system						Ι						Ι
Engine coolant	Replace at first 168,000km (105,000miles) or 60 months ; after that, every 48,000km (30,000miles) or 24 months											
Engine coolant level	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι

FUEL SYSTEM

Air filter	Puerto Rico			R				
All Inter	Others				R			
Fuel lines and hoses ^{*1}				Ι				Ι
Hoses and tubes for emi	ssion ^{*1}							Ι

IGNITION SYSTEM

Consultant and	rk plugs	Replace every 96,000km (60,000miles)
Spark plugs	Others ^{*2}	Replace every 120,000km (75,000miles)

ELECTRICAL SYSTEM

Function of all lights	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι
*1						-			-	-		

*1 According to state/provincial and federal regulations, failure to perform maintenance on these items will not void your emissions warranties. However, Mazda recommends that all maintenance services be performed at the recommended time or mileage/kilometer period to ensure long-term reliability.
*2 If the vehicle is operated under any of the following conditions, change the spark plugs every 96,000 km(60,000 miles) or shorter.
a)Repeated short-distance driving b)Extended periods of idling or low-speed operation c)Driving for long periods in cold temperatures or extremely humid climates

I : Inspect and repair, clean, adjust, or replace if necessary. L: Lubricate

Maintenance Interval	Months	4	8	12	16	20	24	28	32	36	40	44	48
(Number of months or kilometers (miles),	×1000 km	8	16	24	32	40	48	56	64	72	80	88	96
whichever comes first)	×1000 miles	5	10	15	20	25	30	35	40	45	50	55	60

CHASSIS and BODY

Brake lines, hoses and connections						Ι						Ι
Brake and clutch fluid level	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι
Disc brakes			Ι			Ι			Ι			Ι
Tire inflation pressure and tire wear	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι
Steering operation and linkages						Ι						Ι
Power steering fluid level	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι
Front suspension ball joints						Ι						Ι
Driveshaft dust boots						Ι						Ι
Bolts and nuts on chassis and body			Ι			Ι			Ι			Ι
Exhaust system heat shields						Ι						Ι
All locks and hinges	L	L	L	L	L	L	L	L	L	L	L	L
Washer fluid level	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι	Ι

AIR CONDITIONER SYSTEM (if installed)

Cabin air filter	$D_{\rm cm}$ = $a_{\rm cm}$ = $40,000$ = $(25,000$ = $(1-x)$ = 24 = $a_{\rm cm}$ = 4
Cabin air filter	Replace every 40,000km (25,000miles) or 24 months