

Maintenance and Specifications

SCHEDULED MAINTENANCE

Schedule 1 — Normal Driving Conditions/Emission Control Systems

Follow Schedule 1 if the vehicle is operated mainly where none of the following conditions apply. If any do apply, follow Schedule 2.

- Repeated short-distance driving.
- Driving in dusty conditions.
- Towing a trailer.
- Operating in hot weather in stop-and-go “rush hour” traffic.
- Extended periods of idling or low-speed operation.
- High-speed operation with a fully loaded vehicle.
- Off-road operation.

NOTE: After the described period, continue to follow the described maintenance at the recommended intervals.

Maintenance and Specifications

CHART SYMBOLS

- I** : Inspect and if necessary, correct, clean or replace
- A** Adjust
- R** : Replace
- L** : Lubricate

Normal driving service intervals — perform at the months or distances shown, whichever occurs first.

| Maintenance Item | Maintenance Interval (Number of months or Miles (km), whichever comes first) | | | | | | | | | | | | | |
|---|---|-----|------|------|------|------|------|------|------|------|------|------|------|---|
| | Months | 4 | 8 | 12 | 16 | 20 | 24 | 28 | 32 | 36 | 40 | 44 | 48 | |
| | x 1000 miles | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | |
| | (x 1000 km) | (8) | (16) | (24) | (32) | (40) | (48) | (56) | (64) | (72) | (80) | (88) | (96) | |
| ENGINE | | | | | | | | | | | | | | |
| Engine oil | R | R | R | R | R | R | R | R | R | R | R | R | R | R |
| Oil filter | R | R | R | R | R | R | R | R | R | R | R | R | R | R |
| PCV valve | *3 | | | | | | | | | | | | | |
| AIR CLEANER | | | | | | | | | | | | | | |
| Air cleaner filter | | | | | | | R | | | | | | | R |
| IGNITION SYSTEM | | | | | | | | | | | | | | |
| Spark plugs | *4 | | | | | | | | | | | | | |
| COOLING SYSTEM | | | | | | | | | | | | | | |
| Engine Coolant (yellow) | Replace at first 100,000 miles (160,000 km) or 60 months; after that, every 50,000 miles (80,000 km) or 36 months | | | | | | | | | | | | | |
| Coolant condition and protection, hoses and clamps — annually — prior to cold weather every 12 months | | | I | | | | I | | | | I | | | I |
| CHASSIS AND BODY | | | | | | | | | | | | | | |
| Wheel lug nut torque | *1 | I | I | I | I | I | I | I | I | I | I | I | I | I |
| Inspect tires for wear and rotate (X = recommended interval for optimal tire life) | | I | X | I | X | X | I | X | X | I | X | X | I | |
| Clutch reservoir fluid level | | I | | I | | I | | I | | I | | I | | |
| Front wheel bearings (4x2) | | | | | | | | | | | | | | L |

Maintenance and Specifications

| Maintenance Item | Maintenance Interval (Number of months or Miles (km), whichever comes first) | | | | | | | | | | | | | |
|---|--|-----|------|------|------|------|------|------|------|------|------|------|------|--|
| | Months | 4 | 8 | 12 | 16 | 20 | 24 | 28 | 32 | 36 | 40 | 44 | 48 | |
| | x 1000 miles | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | |
| | (x 1000 km) | (8) | (16) | (24) | (32) | (40) | (48) | (56) | (64) | (72) | (80) | (88) | (96) | |
| Disc brake system | | | | I | | | I | | | I | | | I | |
| Caliper slide rails | | | | L | | | L | | | L | | | L | |
| Drum brake system, lines and hoses | | | | I | | | I | | | I | | | I | |
| Exhaust system for leaks, damage, looseness | | | | | | | I | | | | | | I | |
| Manual transmission fluid | | | | | | | | | | | | | R | |
| Automatic transmission fluid | *2 | | | | | | I | | | | | | I | |
| Exhaust system shielding (for trapped material) | | | | | | | I | | | | | | I | |
| Propeller shaft U-joints (if equipped with grease fittings) | L | | L | | L | | L | | L | | L | | L | |
| Parking brake system (for damage and operation) | | | I | | | | I | | | I | | | I | |
| Ball joints (4x2) | | | I/L | | | | I/L | | | I/L | | | I/L | |
| Transfer case fluid (4x4) | Replace every 150,000 miles (240,000 km) | | | | | | | | | | | | | |
| Rear axle lubricant | Does not require replacement unless rear axle submerged in water | | | | | | | | | | | | | |
| Accessory drive belts | | | | | | | | | | | | | | |
| Fuel filter | *5 | | | | | | R | | | | | | R | |
| Steering linkage, ball joints, suspension and driveshaft | | | I | | | | I | | | I | | | I | |

*1 The wheel lug nuts must be retightened to the proper specifications at 500 miles (800 km) of new vehicle operation, at any wheel change, or at any other time the wheel lug nuts have been loosened. Refer to *Wheel Lug Nut Torque Specification* in the *Tires, Wheels and Loading* chapter for the proper lug nut torque specification.

*2 Replace every 150,000 miles (240,000 km) unless submerged in water.

*3 At 60,000 miles (96,000 km), the dealer will replace the PCV valve at no cost, except Canada and California vehicles.

*4 Refer to vehicle emission control information label for spark plug and gap specifications.

Maintenance and Specifications

*5 The California Air Resources Board has determined that the failure to perform this maintenance item will not nullify the emission warranty nor limit recall liability prior to completion of the vehicle's useful life.

Schedule 1 continued

| Maintenance Item | Maintenance Interval (Number of months or Miles (km), whichever comes first) | | | | | | | | | | | | | |
|--|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|---|
| | Months | 52 | 56 | 60 | 64 | 68 | 72 | 76 | 80 | 84 | 88 | 92 | 96 | |
| | x 1000 miles | 65 | 70 | 75 | 80 | 85 | 90 | 95 | 100 | 105 | 110 | 115 | 120 | |
| | (x 1000 km) | (104) | (112) | (121) | (128) | (136) | (144) | (152) | (160) | (168) | (176) | (184) | (192) | |
| ENGINE | | | | | | | | | | | | | | |
| Engine oil | R | R | R | R | R | R | R | R | R | R | R | R | R | R |
| Oil filter | R | R | R | R | R | R | R | R | R | R | R | R | R | R |
| PCV valve | *3 | | | | | | | | | | | | | |
| AIR CLEANER | | | | | | | | | | | | | | |
| Air cleaner filter | | | | | | | R | | | | | | | R |
| IGNITION SYSTEM | | | | | | | | | | | | | | |
| Spark plugs | *4 | | | | | | | | R | | | | | |
| COOLING SYSTEM | | | | | | | | | | | | | | |
| Engine Coolant (yellow) | Replace at first 100,000 miles (160,000 km) or 60 months; after that, every 50,000 miles (80,000 km) or 36 months | | | | | | | | | | | | | |
| Coolant condition and protection, hoses and clamps — annually —prior to cold weather every 12 months | | | I | | | | I | | | | I | | | I |
| CHASSIS AND BODY | | | | | | | | | | | | | | |
| Wheel lug nut torque | *1 | I | I | I | I | I | I | I | I | I | I | I | I | I |
| Inspect tires for wear and rotate (X = recommended interval for optimal tire life) | X | X | I | X | X | I | X | X | I | X | X | I | X | I |
| Clutch reservoir fluid level | I | | I | | | I | | | I | | I | | I | |
| Front wheel bearings (4x2) | | | | | | | | | | | | | | L |
| Disc brake system | | | I | | | | I | | | | I | | | I |
| Caliper slide rails | | | L | | | | L | | | | L | | | L |
| Drum brake system, lines and hoses | | | I | | | | I | | | | I | | | I |

Maintenance and Specifications

| Maintenance Item | Maintenance Interval (Number of months or Miles (km), whichever comes first) | | | | | | | | | | | | | |
|---|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| | Months | 52 | 56 | 60 | 64 | 68 | 72 | 76 | 80 | 84 | 88 | 92 | 96 | |
| | x 1000 miles | 65 | 70 | 75 | 80 | 85 | 90 | 95 | 100 | 105 | 110 | 115 | 120 | |
| | (x 1000 km) | (104) | (112) | (121) | (128) | (136) | (144) | (152) | (160) | (168) | (176) | (184) | (192) | |
| Exhaust system for leaks, damage, looseness | | | | | | | I | | | | | | I | |
| Manual transmission fluid | | | | | | | | | | | | | R | |
| Automatic transmission fluid *2 | | | | | | | I | | | | | | I | |
| Exhaust system shielding (for trapped material) | | | | | | | I | | | | | | I | |
| Propeller shaft U-joints (if equipped with grease fittings) | L | | L | | L | | L | | L | | L | | | |
| Parking brake system (for damage and operation) | | | I | | | | I | | | I | | | I | |
| Ball joints (4x2) | | | I/L | | | | I/L | | | I/L | | | I/L | |
| Transfer case fluid (4x4) | Replace every 150,000 miles (240,000 km) | | | | | | | | | | | | | |
| Rear axle lubricant | Does not require replacement unless rear axle submerged in water | | | | | | | | | | | | | |
| Accessory drive belts | | | | | | | | | I | | | | | |
| Fuel filter *5 | | | | | | | R | | | | | | R | |
| Steering linkage, ball joints, suspension and driveshaft | | | I | | | | I | | | I | | | I | |

*1 The wheel lug nuts must be retightened to the proper specifications at 500 miles (800 km) of new vehicle operation, at any wheel change, or at any other time the wheel lug nuts have been loosened. Refer to *Wheel Lug Nut Torque Specification* in the *Tires, Wheels and Loading* chapter for the proper lug nut torque specification.

*2 Replace every 150,000 miles (240,000 km) unless submerged in water.

*3 At 60,000 miles (96,000 km), the dealer will replace the PCV valve at no cost, except Canada and California vehicles.

*4 Refer to vehicle emission control information label for spark plug and gap specifications.

*5 The California Air Resources Board has determined that the failure to perform this maintenance item will not nullify the emission warranty nor limit recall liability prior to completion of the vehicle's useful life.

Maintenance and Specifications

SCHEDULE 2 — SPECIAL OPERATING CONDITIONS

If your driving habits **FREQUENTLY** include one or more of the following conditions:

- Short trips of less than 10 miles (16 km) when outside temperatures remain below freezing.
- Towing a trailer, or carrying maximum loads.
- Operating in severe dust conditions.
- Operating during **hot weather** in stop-and-go “rush hour” traffic.
- Extensive idling, such as police, taxi or door-to-door delivery service.
- High speed operation with a fully loaded vehicle (max. GVW).
- Off-road operation

Change ENGINE OIL AND OIL FILTER every 3 months or 3,000 miles (4,800 km) whichever occurs first.

NOTE: Idling the engine for extended periods will accumulate more hours of use on your vehicle than is actually indicated by the mileage odometer. Consequently, the odometer reading can be often misleading when determining the right time to change your engine oil and filter. If you are using your vehicle in a manner which allows it to remain stationary while the engine is running for long periods (door-to-door delivery, taxi, police, power/utility company trucks, or similar duty), then Mazda recommends you increase the frequency of oil and filter changes to an interval equivalent to 200 ENGINE HOURS or use. Since most vehicles are not equipped with hour-meters, it may be necessary for you to approximate your idle time and plan oil/filter changes accordingly.

Maintenance and Specifications

| Special Operating Conditions | Replace Engine Oil and Filter | Inspect Brake System | Replace Fuel Filter | Change Automatic Transmission Fluid | Replace Spark Plugs | Replace Engine Air Filter | Change Manual Transmission Fluid | Inspect and Lubricate U-Joints | Lubricate Front Wheel Bearing (4x2) | Change Transfer Case Fluid (4x4) |
|--|-------------------------------|----------------------|---------------------|-------------------------------------|---------------------|---------------------------|----------------------------------|--------------------------------|-------------------------------------|----------------------------------|
| Suggested Maintenance Interval | 3,000 miles or 3 months | 5,000 miles | 15,000 miles | 30,000 miles | 60,000 miles | As required | As required | As required | 30,000 miles | 60,000 miles |
| Towing a trailer or using a camper or car top carrier | X | | | X | | X | X | | | |
| Extensive idling or low-speed driving for long distances as in heavy commercial use such as delivery, taxi or patrol car | X | X | X | X | X | | | | X | X |
| Operating in dusty conditions such as unpaved or dusty roads | X | | X | X | | X | | | | |
| Off road operation | | | | X | | | | X | | X |

For specific recommendations see your authorized Mazda dealer or qualified service professional.

OWNER MAINTENANCE

Owner Maintenance Schedule

The owner or a qualified service technician should make these vehicle inspections at the indicated intervals to ensure safe and dependable operation.

Bring any problem to the attention of an Authorized Mazda Dealer or qualified service technician as soon as possible.